

# 60 ÖKOALPIN





## Technical data (Data may vary depending on type of fuel used)

Fuel	Wood
Energy class	A+
Heating capacity	6 kW / 5160 Kcal
Performance	80.2 %
Diameter smoke outlet	Ø 120 mm
Minimum draught	12 Pa / 0.12 mbar
Temperature smoke outlet	265 °C
Smoke mass	8.3 g/s
CO at 13% O <sub>2</sub>	0.07 %
Weight	140 kg
Optional smoke outlet	8
Test report	IMQ CPD-11-025
VKF AEAI - No.	16684
Firebox opening Trend/Dekor version (L x H)	200 x 165 mm
Firebox opening Panorama version (L x H)	205 x 180 mm
Firebox measurements (L x D x H)	210 x 320 x 260 mm
Drawer measurements (L x D x H)	340 x 420 x 290 mm
Oven (L x D x H)	-
Cooking hob (L x D)	500 x 500 mm
External air intake	Ø 80 mm
CO at 13% O <sub>2</sub> (Carbon monoxide) / NO <sub>x</sub> (Nitrogen oxide)	85.0 mg/Nm <sup>3</sup> / 58.0 mg/MJ
Dust / OGC (Organic compounds)	39.0 mg/Nm <sup>3</sup> / 43.0 mg/MJ


## WARNING: Minimum safety distance from flammable materials

From the rear and side connection to the chimney * 40mm of insulation with heat conductivity equal to 0.07 W/mK at 200°C	P= 0 + 40* mm Following agreement with chimney sweep
On the side above the plate	L= 500 mm
On the side below the plate	L= 3 mm
Above the plate	Min. 750 mm
In the front from the middle of the fire door	R= 250 mm
Plate for floor protection	Based on specific country directives

**NB:** Available in right and left version



Also available with smoke deviation valve. In this case, the combustion chamber will be moved to the right or left depending on the position requested.



Ein Unternehmen aus  
**SÜDTIROL**