

# 60 PREFABRICATED

## Technical data (Data may vary depending on type of fuel used)

Fuel	Wood
Energy class	A+
Heating capacity	6 kW
Performance	80,2 %
Diameter smoke outlet	Ø 120 mm
Minimum draught	12 Pa / 0,12 mbar
Temperature smoke outlet	265 °C
Smoke mass	8,3 g/s
CO at 13% O <sub>2</sub>	0,07 %
Weight	110 kg
Optional smoke outlet	8
Test report	CPD-11-025
VKF AEA1 - No.	16684
Firebox opening Trend/Dekor version (L x H)	200 x 165 mm
Firebox opening Panorama version (L x H)	205 x 180 mm
Firebox measurements (L x D x H)	210 x 330 x 260 mm
Drawer measurements (L x D x H)	-
Oven (L x D x H)	-
Cooking hob (L x D)	450 x 460 mm
External air intake	Ø 80 mm
CO at 13% O <sub>2</sub> (Carbon monoxide) / NO <sub>x</sub> (Nitrogen oxide)	857,0 mg/Nm <sup>3</sup> / 58,0 mg/MJ
Dust / OGC (Organic compounds)	39,0 mg/Nm <sup>3</sup> / 43,0 mg/MJ





## WARNING: Minimum safety distance from flammable materials

From the rear and side connection to the chimney * 40mm of insulation with heat conductivity equal to 0.07 W/mK at 200°C	P= 0 + 40* mm Following agreement with chimney sweep
On the side above the plate	L= 500 mm
On the side below the plate (only with Air System fireproof protection unit)	L= 3 mm
Above the plate	Min. 750 mm
In the front from the middle of the fire door	R= 250 mm
Plate for floor protection	Based on specific country directives

**NB:** Available in right and left version

On request with Air System fireproof protection unit (optional)

On request with walls built and plastered (optional)



Also available with smoke deviation valve.

